

# THE IMPACT of SUMP PUMP FLOWS

The impact of sump pump flows on a sewer system can be significant. These additional flows will create sanitary sewer overflows (SSO's). The following illustrates the impact of sump pump flows:

## The Facts:

- The average homeowner sump pump is between 1/3 and 1/2 horsepower.
- The average discharge rate is between 2500 to 3200 gallons per hour (gph) or 42 to 53 gallons per minute (gpm).

## The Example:

- Using the low-end pumping rate of 42 gpm
- Using an average pump time of 5 minutes per hour
- Using 50 sump pump connections

During a wet weather event (substantial rain, snow melt) the following can be assumed:

$42 \text{ gpm} \times 5 \text{ mins/hr} = 210 \text{ gallons per hour/connection}$

$210 \text{ gph} \times 24 \text{ hrs/day} = 5040 \text{ gallons per day/connection}$

$5040 \text{ gpd/connection} \times 50 \text{ connections} = \underline{\underline{252000 \text{ gallons per day extra flow!}}}$

That's 252000 gallons a day in addition to the usual daily flow.

## What Can You Do?

1. Disconnect sump pumps from the sanitary sewer. Connect them to a storm sewer, drainage ditch, or dry well.
2. Urge your neighbors to do the same. It will save you money in the long run.
3. If you have any questions regarding a sump pump connection, call the office. They will be happy to assist you.